

An affordable, stationary, ambient air quality monitor that measures particulate matter, temperature and relative humidity

FEATURES

- · IoT technology
- · Real-time air quality data transmission
- On-device LCD screen that displays real- • time data
- ·WiFi | GPS | 4G*
- In-built memory of 32GB
- Battery backup (6-7 hours, 12-14 hours*) . Solar compatible device*
- · Data frequency of 1 minute (default)



MSTALLATION: Is easy and last mile deployments can be made available on request.

MAINTAINANCE: Sensors require minimal maintenance as they are pre-calibrated in factories. Replacement of sensors is easy and as per requirements.

DATA ACCESS: Data can be accessed through
1. SD card (manually or wirelessly)
2. API links
3. Cloud-based analytics dashboard (cluster map visualisations, averaging feature & statistical analysis)

ANTY: The sensors are covered for up to one year against manufacturing defects.

WEATHERPROOF: The devices use an IP65 enclosure but to provide additional protection to airvents a weatherproof case* can be provided.

Saksham Scientific Instruments Pvt. Ltd

1203-A Wing, Kailas Business Park Veer Savarkar Road, Near Kailas Industrial Complex, Opp. HDFC Bank, Vikhroll(W), Mumbai-400 079

Call: 9821241942 | Email: kamlesh@ssipl.net.in

PRODUCT SPECIFICATIONS

Dimensions: 170x125x67 mm

Weight: 400 gms

Accessories: Adaptor(5v,2A) x 1, Charging Cable (106 cm) x 1, Mounting wall clamper x 2, Cable zip tie x 2, Power rating: 5V, 2A (max.)

SENSOR SPECIFICATIONS

Particulate matter (PM1, PM2.5 & PM10)

- Detection method: Laser scattering
- Detection threshold: 0 to 1,000 μg/m3
- Resolution: 1 µg/m3
- Accuracy: ~0.8R2, ~MAPE 15%

Ambient Temperature

- Detection threshold: -10 to 45 deg C
- Resolution: 0.5 deg C
- Accuracy ± 0.5 deg C

Ambient Relative humidity

- · Detection threshold: 0 to 100%
- Resolution: 1% Accuracy ± 1%

ADD-ON SENSORS*

Noise, Carbon monoxide, Carbon dioxide, Sulphur dioxide, Nitrogen dioxide, Ozone, Total volatile organic compounds, Formaldehyde